Maximum Segment Sum

Nils Cremer

February 6, 2026

Abstract

In this work we consider the *maximum segment sum* problem [1], that is to compute, given a list of numbers, the largest of the sums of the contiguous segments of that list. We assume that the elements of the list are not necessarily numbers but just elements of some linearly ordered group. Both an implementation for a naive algorithm ($\mathcal{O}(n^2)$) as well as for Kadane's algorithm [1] ($\mathcal{O}(n)$) are given and their correctness proven.

Contents

1 Maximum Segment Sum **1**
1.1 Naive Solution 2
1.2 Kadane's Algorithms 3

1 Maximum Segment Sum

theory *Maximum-Segment-Sum*
imports *Main*
begin

The *maximum segment sum* problem is to compute, given a list of numbers, the largest of the sums of the contiguous segments of that list. It is also known as the *maximum sum subarray* problem and has been considered many times in the literature; the Wikipedia article Maximum subarray problem is a good starting point.

We assume that the elements of the list are not necessarily numbers but just elements of some linearly ordered group.

class *linordered-group-add* = *linorder* + *group-add* +
assumes *add-left-mono*: $a \leq b \Longrightarrow c + a \leq c + b$
assumes *add-right-mono*: $a \leq b \Longrightarrow a + c \leq b + c$
begin

lemma *max-add-distrib-left*: *max* y z + x = *max* (y+x) (z+x)

⟨*proof*⟩

lemma *max-add-distrib-right*: $x + max\ y\ z = max\ (x+y)\ (x+z)$
⟨*proof*⟩

1.1 Naive Solution

fun *mss-rec-naive-aux* :: *'a list* ⇒ *'a* **where**
  mss-rec-naive-aux [] = *0*
| *mss-rec-naive-aux* (*x*#*xs*) = *max 0* (*x* + *mss-rec-naive-aux xs*)

fun *mss-rec-naive* :: *'a list* ⇒ *'a* **where**
  mss-rec-naive [] = *0*
| *mss-rec-naive* (*x*#*xs*) = *max* (*mss-rec-naive-aux* (*x*#*xs*)) (*mss-rec-naive xs*)

definition *fronts* :: *'a list* ⇒ *'a list set* **where**
  fronts xs = {*as*. ∃ *bs*. *xs* = *as* @ *bs*}

definition *front-sums xs* ≡ *sum-list* ' *fronts xs*

lemma *fronts-cons*: *fronts* (*x*#*xs*) = ((#) *x*) ' *fronts xs* ∪ {[]} (**is** *?l* = *?r*)
⟨*proof*⟩

lemma *front-sums-cons*: *front-sums* (*x*#*xs*) = (+) *x* ' *front-sums xs* ∪ {*0*}
⟨*proof*⟩

lemma *finite-fronts*: *finite* (*fronts xs*)
  ⟨*proof*⟩

lemma *finite-front-sums*: *finite* (*front-sums xs*)
  ⟨*proof*⟩

lemma *front-sums-not-empty*: *front-sums xs* ≠ {}
  ⟨*proof*⟩

lemma *max-front-sum*: *Max* (*front-sums* (*x*#*xs*)) = *max 0* (*x* + *Max* (*front-sums xs*))
⟨*proof*⟩

lemma *mss-rec-naive-aux-front-sums*: *mss-rec-naive-aux xs* = *Max* (*front-sums xs*)
⟨*proof*⟩

lemma *front-sums*: *front-sums xs* = {*s*. ∃ *as bs*. *xs* = *as* @ *bs* ∧ *s* = *sum-list as*}
⟨*proof*⟩

lemma *mss-rec-naive-aux*: *mss-rec-naive-aux xs* = *Max* {*s*. ∃ *as bs*. *xs* = *as* @ *bs* ∧ *s* = *sum-list as*}
⟨*proof*⟩

definition *mids* :: *'a list* ⇒ *'a list set* **where**
mids xs ≡ {*bs*. ∃ *as cs*. *xs* = *as* @ *bs* @ *cs*}

definition *mid-sums xs* ≡ *sum-list* ‘ *mids xs*

lemma *fronts-mids*: *bs* ∈ *fronts xs* ⟹ *bs* ∈ *mids xs*
⟨*proof*⟩

lemma *mids-mids-cons*: *bs* ∈ *mids xs* ⟹ *bs* ∈ *mids* (*x*#*xs*)
⟨*proof*⟩

lemma *mids-cons*: *mids* (*x*#*xs*) = *fronts* (*x*#*xs*) ∪ *mids xs* (**is** *?l* = *?r*)
⟨*proof*⟩

lemma *mid-sums-cons*: *mid-sums* (*x*#*xs*) = *front-sums* (*x*#*xs*) ∪ *mid-sums xs*
⟨*proof*⟩

lemma *finite-mids*: *finite* (*mids xs*)
⟨*proof*⟩

lemma *finite-mid-sums*: *finite* (*mid-sums xs*)
⟨*proof*⟩

lemma *mid-sums-not-empty*: *mid-sums xs* ≠ {}
⟨*proof*⟩

lemma *max-mid-sums-cons*: *Max* (*mid-sums* (*x*#*xs*)) = *max* (*Max* (*front-sums* (*x*#*xs*))) (*Max* (*mid-sums xs*))
⟨*proof*⟩

lemma *mss-rec-naive-max-mid-sum*: *mss-rec-naive xs* = *Max* (*mid-sums xs*)
⟨*proof*⟩

lemma *mid-sums*: *mid-sums xs* = {*s*. ∃ *as bs cs*. *xs* = *as* @ *bs* @ *cs* ∧ *s* = *sum-list bs*}
⟨*proof*⟩

theorem *mss-rec-naive*: *mss-rec-naive xs* = *Max* {*s*. ∃ *as bs cs*. *xs* = *as* @ *bs* @ *cs* ∧ *s* = *sum-list bs*}
⟨*proof*⟩

1.2 Kadane's Algorithms

fun *kadane* :: *'a list* ⇒ *'a* ⇒ *'a* ⇒ *'a* **where**
kadane [] *cur m* = *m*
| *kadane* (*x*#*xs*) *cur m* =
(*let cur'* = *max* (*cur* + *x*) *x in*
kadane xs cur' (*max m cur'*))

definition *mss-kadane xs* ≡ *kadane xs 0 0*

lemma *Max-front-sums-geq-0*: *Max* (*front-sums xs*) ≥ *0*
⟨*proof*⟩

lemma *Max-mid-sums-geq-0*: *Max* (*mid-sums xs*) ≥ *0*
⟨*proof*⟩

lemma *kadane*: *m* ≥ *cur* ⟹ *m* ≥ *0* ⟹ *kadane xs cur m* = *max m* (*max* (*cur* + *Max* (*front-sums xs*)) (*Max* (*mid-sums xs*)))
⟨*proof*⟩

lemma *Max-front-sums-leq-Max-mid-sums*: *Max* (*front-sums xs*) ≤ *Max* (*mid-sums xs*)
⟨*proof*⟩

lemma *mss-kadane-mid-sums*: *mss-kadane xs* = *Max* (*mid-sums xs*)
⟨*proof*⟩

theorem *mss-kadane*: *mss-kadane xs* = *Max* {*s*. ∃ *as bs cs*. *xs* = *as* @ *bs* @ *cs* ∧ *s* = *sum-list bs*}
⟨*proof*⟩

end

end

References

[1] Wikipedia. Maximum subarray problem, 2022. [https://en.wikipedia.org/wiki/Maximum_subarray_problem; accessed 25-September-2022].